

# ECO R II



**ATTENTION DISCONTINUED PRODUCT.** Fundamental Finnish luminaire know-how. Excellent LEDs (180 lm/W), reliable electronic control gear and the structure of the luminaire designed on terms the components offers efficient yet very energy-efficient and reliable end result. 1-10V dimming makes your luminaire a part of a smart lighting.

## Benefits

IP65 rated luminaire that withstands the most difficult environment, with easy and quick installation. High impact resistance with IK08 classification. Key to the extremely cost-efficient lighting solution. Electronic control gear outside of the luminaire body guarantees a long lifetime and makes maintenance easy.

## Suitability

A generic luminaire for several purposes that is suitable for parking halls, storages, industrial halls, stores and shelters.

## Product families and variants

MODEL	TYPE CODE	POWER	LUMINOUS FLUX	LUMINAIRE EFFICACY	LIFETIME	OPERATING TEMPERATURE
Eco R II 35 W	GLR92350	35 W	4600 lm	131 lm/W	L80 > 80000 h	-40 - +55°C

### Notes:

All values in ambient temperature of +25°C, CCT 4000K, luminous flux tolerance +-5%, output power tolerance +-5%.


## Dimensions

MODEL	TYPE CODE	LENGTH (L)	HEIGHT (H)	WIDTH (W)	WEIGHT
Eco R II 35 W	GLR92350	1093 mm	77 mm	41 mm	1,7 kg


## General Description

<b>COLOUR TEMPERATURE:</b>	4000 K
<b>COLOUR RENDERING INDEX:</b>	$R_A \geq 80$
<b>OPTIC:</b>	Frosty or transparent
<b>LIGHT SOURCE SHIELD:</b>	PC
<b>IP CLASS:</b>	IP 65
<b>SUPPLY VOLTAGE:</b>	100-240 Vac
<b>FREQUENCY:</b>	50-60 Hz
<b>PF:</b>	> 0.9
<b>THD:</b>	20%
<b>CONNECTION:</b>	Input: 3-pole rubber installation cable,3m
<b>DIMMABILITY:</b>	1-10V
<b>COLOUR:</b>	Grey aluminium
<b>MATERIAL OF THE LUMINAIRE BODY:</b>	Aluminum
<b>GARANTEE:</b>	5 years
<b>ACCESSORIES (INSTALLATION):</b>	3508141 Bracket for Horizontal Wire, 3508012 MEK 70 rail bracket, 3508014 MEK 82 suspension rail bracket, 3508013 MEK 110 suspension rail bracket, 3508010 Surface mounting bracket

## Light distribution




## Dimensions




## Brackets


3508141 Bracket for Horizontal Wire




3508012 MEK 70 rail bracket




3508014 MEK 82 suspension rail bracket



3508013 MEK 110 suspension rail bracket



3508010 Surface mounting bracket



## Circuit breakers

	B10	B16	B20	C10	C16	C20
ECO R II 35 W	10	15	19	16	25	31

i

### CUSTOMER SERVICE:

tel: +358 20 125 5800

info@greenled.fi